

Catalogue de requêtes génériques

Block Dashboard (Elément de tableau de bord)

Tableau de popularité des ressources par cohortes

Affiche un tableau de popularité des ressources par cohortes. Rendu en colonnes de sortie avec l'affichage par catégorie et sous-catégorie de cours, type et nom des ressources avec nombre de vues et date de dernière visualisation par ressource, ainsi que les sections et sous-sections ou elles figurent.

SELECT

```
CONCAT(cm.id, '-', ch.id) as pkey,  
cm.id,  
c.shortname as cs,  
c.fullname as cf,  
cc1.name as cc1,  
cc2.name as cc2,  
cs1.name as cs1,  
cs2.name as cs2,  
ch.name as ch,  
m.name as rtype,  
CASE WHEN m.name = 'resource' THEN r.name  
      WHEN m.name = 'page' THEN p.name  
      WHEN m.name = 'url' THEN ur.name  
      WHEN m.name = 'quiz' THEN q.name  
      WHEN m.name = 'workshop' THEN w.name  
      WHEN m.name = 'folder' THEN f.name ELSE 'N.C.' END as rname,  
CASE WHEN ltci.itemoptional = 0 THEN 'Obligatoire' ELSE 'Facultatif' END as  
cmst,  
COUNT(DISTINCT ltcc.userid) as dusers,  
COUNT(*) as views,  
MAX(l.timecreated) as lastview
```

FROM

```
{modules} m,  
{learningtimecheck_item} ltci,  
{learningtimecheck_check} ltcc,  
{course} c,  
{course_categories} cc1,  
{course_categories} cc2,  
{logstore_standard_log} l,  
{cohort} ch,  
{cohort_members} chm,  
{course_modules} cm
```

LEFT JOIN

```
{resource} r
```

ON

```
r.id = cm.instance
```

LEFT JOIN

```
{url} ur
```

ON

```
ur.id = cm.instance
```

LEFT JOIN

```
{folder} f
```

ON

```
f.id = cm.instance
```

LEFT JOIN

```
{quiz} q
```

ON

```
q.id = cm.instance
```

LEFT JOIN

```
{page} p
```

ON

```
p.id = cm.instance
```

LEFT JOIN

```
{workshop} w
```

ON

```
w.id = cm.instance
```

LEFT JOIN

```
{course_sections} cs1
```

ON

```
cm.section = cs1.id
```

LEFT JOIN

```
{course_format_options} cfo
```

ON

```
cs1.id = cfo.sectionid
```

LEFT JOIN

```
{course_sections} cs2
```

ON

```
cs2.section = cfo.value AND  
cfo.courseid = cs2.course
```

WHERE

```
m.id = cm.module AND  
m.name IN('resource', 'page', 'url', 'folder', 'quiz') AND  
ltcc.item = ltci.id AND  
ltci.moduleid = cm.id AND  
ltcc.userid = chm.userid AND  
cm.course = c.id AND  
cc1.id = c.category AND  
cc2.id = cc1.parent AND  
ch.id = chm.cohortid AND  
ltcc.userid = l.userid AND  
l.objecttable = m.name AND  
l.objectid = cm.instance AND  
l.action = 'viewed'  
<%%FILTERS%%>
```

GROUP BY

```
CONCAT(cm.id, '-', ch.id)
```

Configuration

Tzo4OijzdGRDbGFzcyI6OTg6e3M6NToidGI0bGUiO3M6NDQ6IIBvcHVzYXJpdMOplGRlcyByZXNzb3VyY2V

